4-WHEEL SCOOTER



ENGINEERED FOR POWERFUL PERFORMANCE AND EXCEPTIONAL STYLE

The **Pursuit® XL** is an exciting blend of power and precision that features a 24-volt DC motor, full suspension, 13" low-profile tires and a hydraulic-sealed brake system. Standard luxury touches like an infinite adjustable wraparound delta tiller, high-back pillow top seat and LED lighting make it the perfect outdoor scooter.







Full Suspension









SPECIFICATIONS

Maximum speed ¹ : U	25" 2.5"
	25"
0	
Ground clearance ² : 5.	2.5"
Turning radius: 82	
Overall length ² : 56	5"
Overall width ² : 27	7.25"
Front tires: 13	3" pneumatic
Rear tires: 13	3" pneumatic
Suspension: Fr	ront and Rear
	roup 24 (70 AH): Up to 22.13 miles roup 27 (100 AH): Up to 29.51 miles
Total weight 25 without batteries:	53.9 lbs. (without batteries)
Heaviest piece when North disassembled:	/A
W	ype: High-back pillow top with sliders and headrest /eight: 49 lbs. aterial: Black Vinyl imensions: 19.5" x 16"
Drive system:	ear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes: Re	egenerative and electromechanical
	ize: Group 24 (75 AH), Group 27 (100 AH) /eight⁴: Group 24: 53 lbs. each, Group 27: 60 lbs. each
Battery charger: 8-	amp, off-board

FEATURES

- Infinitely-adjustable tiller angle with conveniently located handle
- Powerful drivetrain; features 200 amp microprocessor-based controller
- Deluxe reclining high-back seat with headrest, sliders, lumbar support, width, height and adjustable arms
- Full lighting package that includes directional signals and lower headlight
- Delta tiller with wraparound handles
- · Large 13" low-profile, pneumatic tires for excellent outdoor performance
- · Front and rear suspension
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- Rearview mirror standard
- Hydraulic handbrake

OPTIONS

- · Rear basket
- · Safety flag
- · Cup holder
- Lap belt
- Saddlebag
- · Weather cover
- Rear view mirror
- · Oxygen holder
- · Walker holder





Color:





Candy Apple Red

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- 3 AGM or gel cell type required.
- 4 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections



